

Certificate of quality

Metalubs X Multi - Anti-wear eco product

Domain: It is recommended for in petrol, diesel, gas, Wankel and turbo engines, hydraulic systems, switch-gears, differential gears, drive gears and industrial equipment in a variety of fields (railways, navigation, power plants, sewing machines, etc.).

Dosage:

Add to the oil at a ratio of 5-10% (minimum 0.5 dl Metalubs X Multi to 1 litre oil) on first treatment. Use it at every oil change. The mixing ratio for second treatment is 2.5%.

Note: suitable only for manual transmission and differential locks! Shake well before use and pour into the hot engine.

Appearance

Physical State:	liquid
Color:	yellowish
Odor:	characteristic

Safety-related data

Flashpoint:	195°C
Ignition temperature at 20°C:	230°C
Vapor pressure:	< 0.1mbar
Density:	1.07 g/cm ³ at 20°C
Bulk density:	not applicable
Water solubility:	insoluble at 20°C
pH-value:	7 to 9
Kinematic viscosity	59 mm ² /s at 40°C
Flammability (solid, gaseous):	Not flammable
Oxidizing properties:	Not oxidizing
Auto-ignition temperature:	Not self-igniting
Melting point/melting range:	< -5°C
Solubility in other solvents:	Well soluble in most oils

TÜV certificate.

The products are made in Germany for Metalubs LTD, who is responsible and offers warranty for the distributed products.

