

# Certificate of quality

## Metalubs X Protect - Anti-wear eco product

**Domain:** The specially developed, environment friendly Metalubs X Protect is particularly suitable for use in new, used petrol, diesel, gas and turbocharged engines.

**Dosage:**

Replace between 5-10% of the engine oil, and 10% of the transmission oil with Metalubs X Protect.

**Note:** X Protect suitable only for manual transmission and differential locks! Shake well before use and pour into the hot engine.

**Appearance**

Physical State:	liquid
Color:	white
Odor:	characteristic

**Safety-related data**

Flashpoint:	207°C
Ignition temperature:	410°C
Vapor pressure at 20°C:	< 0.1 mbar
Density at 20°C:	1.02 g/cm <sup>3</sup>
Water solubility:	insoluble at 20°C
pH-value:	7 to 9
Kinematic viscosity at 40°C	56 mm <sup>2</sup> /s
Flammability (solid, gaseous):	Not flammable
Oxidizing properties:	Not oxidizing
Auto-ignition temperature:	Not self-igniting
Melting point/melting range:	< -5°C
Solubility in other solvents:	Well soluble in most oils

**TÜV certificate.**

The products are made in Germany for Metalubs LTD, who is responsible and offers warranty for the distributed products.

